TYVEK PROTEC 160 ROOFING UNDERLAYMENT




INDUSTRY-LEADING WALKABILITY The unique embossed pattern allows for better traction and grip while walking on the roof.



TRUSTED QUALITY AND DURABILITY

Another innovative material breakthrough from DuPont[™] Tyvek[®], the leader in building envelope systems.



A FAMILY OF UNDERLAYMENTS Our portfolio of roofing underlayments provides choices to better meet your needs.

Industry-leading walkability in dry, wet, hot, cold and dirty conditions.

Tyvek[®] Protec[™] 160 is an engineered synthetic roofing underlayment with industry-leading walkability from DuPont, the trusted name in total building envelope solutions. Ideal for slopes 2:12 or higher under a variety of roofing materials in repair, re-roofing and new construction.

Tyvek[®] Protec[™]



| Walkability | Best in Class |
|------------------------|---------------|
| Roll Size (10 square) | 48" x 250' |
| Rolls Per Pallet | 36 |
| Roll Weight | 31 lbs |
| Warranty | 40 years |
| UV Exposure | 6 months |
| Roof Types | |
| Asphalt Shingle | ~ |
| Cedar Shingle | ~ |
| Metal | ~ |
| Tile | ~ |
| Slate | ~ |
| Recyclable | ~ |
| ASTM D226 Types I & II | ~ |
| ES ICC-ES AC188 | ~ |
| Class A Per ASTM E108 | ~ |
| | |



tyvek.com/protec 1-800-44-TYVEK

Industry-leading walkability when compared to other low permeability synthetic roofing underlayments.

Copyright © 2016 DuPont. All rights reserved. The DuPont Oval Logo, DuPont", For Greater Good", Tyvek" and Tyvek" Protec" are trademarks or registered trademarks of E.I. du Pont de Nemours and Company or its affiliates. K-29379 (07/16)



Easy to chalk Accepts and holds chalk marks for more visible lines and a better finished product.



Protects the roof Preserves the roof deck during installation and provides an effective secondary moisture barrier.

Four-layer construction

-Top layer provides ideal grip and features grooves for dirt and water flow.

Lamination layer acts as a barrier to water.

Woven polypropylene scrim provides strength.

Slip-resistant coating provides grip to the roof deck.



Wrinkle-free Lays flat and stays flat for a more uniform shingled surface.



Supported by the DuPont[™] Tyvek[®] Specialist Network Specialists are available across the U.S. and Canada for additional

knowledge and support.



