

2025 PRODUCT CATALOG

HVAC/R INDUSTRY

ATLANTIC CHEMICAL & EQUIPMENT COMPANY







WHAT'S NEW FOR 2025?

MONSTER SERIES



- MORE CLEANING POWER
- HIGH FOAMABILITY
- STRONGER BRIGHTENING POWER
- FRESH ORANGE DEODORIZING SCENT



SPECIFIC FOR MICRO CHANNEL UNITS
 SAFE FOR RUBBER ROOFS AND ROOFTOP
 NEUTRAL PH – NON-CORROSIVE
 ENVIRONMENTALLY SAFE

TABLE OF CONTENTS

TABLE OF CONTENTS	100 March 100 Ma
Leak Sealants	
Refrigerants	
Refrigerants Line Flushing / Acid Removal	
Coil Cleaners	
Leak Detection	
What's New	
Cleaning Chart	
Aerosol Products	
IAQ Products	
Condensate Pan Maintenance	
Hoses, Manifolds, Gauges & Accessories	
Odor Control / Miscellaneous	
Degreasing Solvents / Oil Absorbents	
Heat Transfer & Anti-freeze Products	
Shop Towels & Wipes	
Threaded Pipe Products	
Refrigeration Oil Products	
Sprayers	
Insulation Products	
Water Filtration Products	
Follow us on Social Media	



see page 10 and 11 for more information

INNOVATION THAT CREATES QUALITY PRODUCTS AND GROWTH

For further product use instructions/information, refer to the Product Data Sheets or SDS Sheets at www.acechempro.com, or call 1-800-929-2436.

Denotes DOT hazardous product subject to UPS/FedEx shipping surcharges.



3

LEAK SEALANTS

SEALANTS

AceSeal	AceSeal
Instatute TON	TON
Restored Former	Harrison Harrison Lander Lands Haller Spelane
Ace much and a	Ace much







AceSeal EZ LEAK STOP PRO

A range of concentrated refrigerant leak sealants supplied with a hose injection delivery system that makes installation simple, fast and easy. The proven formula seals microscopic leaks without the need to pump down the system... even for R410a applications. The leak sealant is offered in 8 sizes (up to 1/2 ton; 1/2 to1.5 tons; 1.5 to 5 tons; 6-15 tons; 16-30 tons; 31-60 tons; 61-125 tons and 126-250 tons). An All-in-One product (leak sealant/dry/ revitalizer/dye/acid eliminator) is supplied in both 1.5-5 tons and 6-15 tons. A leak sealant/ dye combination is available in all 3 sizes up to 15 tons.

ASEZ-MINIDRY (up to 1/2 ton) - 6/cs Leak Sealant/Dry

ASEZ-MINIDRYUV (up to 1/2 ton) - 6/cs Leak Sealant Dry/Dye

ASEZ-PRO (1/2-1.5 tons) - 6/cs Leak Sealant

ASEZ-PRODYE (1/2-1.5 tons) - 6/cs Leak Sealant w/Dye

ASEZ-PRO+ (1.5-5 tons) - 6/cs Leak Sealant

ASEZ-PRO+3 (1.5-5 tons) (3 pack) - 4/cs Leak Sealant

ASEZ-PRODYE+ (1.5-5 tons) - 6/cs Leak Sealant w/Dye

ASEZ-PRODYE+3 (1.5-5 tons) (3 pack) - 4/cs Leak Sealant w/Dye

ASEZ-PRO+AIO (1.5-5 tons) - 6/cs All-in-One Leak Sealant/Dry/Dye/Revitalizer/ Acid Eliminator

ASEZ-PROULTRA(15) (6-15 tons) - 6/cs Leak Sealant

ASEZ-PROULTRADYE(15) (6-15 tons) - 6/cs Leak Sealant w/Dye

ASEZ-PROULTRAAIO(15) (6-15 tons) - 6/cs All-in-One Leak Sealant/Dry/Dye/Revitalizer/ Acid Eliminator

ASEZ-PROULTRA(30) (16-30 tons) - 6/cs Leak Sealant

ASEZ-PROULTRA(60) (31-60 tons) - ea Leak Sealant

ASEZ-PROULTRA(125) (61-125 tons) - ea Leak Sealant

ASEZ-PROULTRA(250) (126-250 tons) - ea Leak Sealant

DEHYDRATING

AceSeal EZ PRO AceSeal AC/R DRY



ASEZ-DRY (up to 5 tons) - 6/cs

REVITALIZER



lee

performance booster specially formulated to enhance cooling properties of new and old air conditioning and refrigeration systems by reducing mechanical friction. Saves energy and will extend unit working life. Ideal for use on heat pumps. split systems, mini-split units, packaged units, microchannel coils etc.

(up to 5 tons) - 6/cs ASEZ-REV3 (up to 5 tons) - 4/cs

UV DYE



AceSeal EZ PRO AC/R DYE



ASEZ-DYE (up to 5 tons) - 6/cs

ACID REMOVER

AceSeal AC/R ACID Dr. 5

0



Formulated to convert moisture/acid to a synthetic oil. The highly polar molecules in the formula bond with moisture/acid in the system and, through the refrigeration process of going from liquid to vapor, produce a synthetic oil.

ASEZ-ACIDX (up to 5 tons) - 6/cs

ASE7-REV

INJECT KIT



AceSeal EZ PRO **INJECT KIT**

An easy-to-use CO₂ gun designed to inject, ACE EZ PRO Products into A/C unit



eavy Du

lines. Eliminates need for manifold gauges or refrigerant tank. Pack also contains fitting to clean out blocked condensate lines. Kit contains CO2 gun; CO₂ injection hose; 2 CO₂ cartridges and a Condensate Drain Opener attachment.

ASEZ-PROKIT - Sold individually ASEZ-CO2CART- 5pk - 10/cs

Compatible with ALL refrigerants including A2L



For further product use instructions/information, refer to the Product Data Sheets or SDS Sheets at www.acechempro.com, or call 1-800-929-2436. Denotes DOT hazardous product subject to UPS/FedEx shipping surcharges.



ASEZ-PRO+ (1.5-5 tons) - 6/cs Leak Sealant

ASEZ-PR0+3 (1.5-5 tons) (3 pack) - 4/cs Leak Sealant

> ASEZ-REV3 (up to 5 tons) - 4/cs

REFRIGERANTS

REFRIGERANTS



ACE R290



IMPROVES A/C PERFORMANCE

A/C

es Energy

۲,

.....

ONS

with zero ozone depletion potential (ODP)and low global warming potential (GWP). Approved by US EPA with special use restrictions (defined in 40 CFR Part 82.172) for new food refrigerators, food freezers, stand-alone units, some industrial applications and new room air conditioners clearly identified for use with this refrigerant, among other uses as approved by the EPA. This refrigerant may only be used in new equipment specifically designed and identified by EPA for R-290 refrigerant use, and may not be used as a conversion or "retrofit" refrigerant for existing equipment.

R290 - 12x8oz cans per case Also available in 12lb and 20lb cylinders

A non-toxic, refrigerant grade propane



IMPROVES A/C PERFORMANCE



VALVES



R290/R600a REFRIGERATION VALVE

Professional grade R-290 and R600a top mount can actuator with shutoff. It is an easy to use, can tap dispenser. Heavy-duty design to connect the refrigerant can to the blue manifold gauge charging hose.

5028-1- Sold Individually




ACE R600a

A non-toxic Refrigerant Grade



R600a - 12x6oz cans per case



Compatible with ALL refrigerants including A2L



5

REFRIGERANT LINE FLUSHING/ACID REMOVAL



ACE[®] POWER FLUSH[®] (APF)*


Powerful ozone-friendly solvent for flushing HVAC/R systems after compressor burn-outs and during retrofits / oil changes. Leaves no residue and is safe for use with systems using all oils and refrigerants. Is non-flammable. Ideal for flushing lines after conversion to R-410A. Use with ACE[®] Flush Injection Tool (AFT) (not included).

APF16 – 16 oz. - 6/cs (for systems from 5 to 7 tons capacity)



POWER FLUSH® II (APFA)*

Ready-to-use, pre-pressurized can containing nonflammable, ozone friendly, non-toxic flushing compound. Cleans HVAC/R systems after compressor burn-outs and during retrofits/oil changes. Ideal for "saving" linesets for 410A conversions. Non-residual solvent safe for use with all oils and refrigerants.





ACE® FLUSH INJECTION TOOL (AFT)

Flush contaminated HVAC/R systems quickly, easily and economically with the injection tool. Re-usable tank comes with an injection gun that allows user to inject system without need for access valves or manifold gauges. Uses dry nitrogen (not included) for propellant. Holds enough ACE[®] Power Flush[®] to clean a 25 ton system.

AFT – Sold individually



POWER FLUSH® INJECTION VALVE

Injection valve for use with Power Flush® II to release solvent into system. Combines with Power Flush® Hose and Power Flush® Injection Gun. Use with Power Flush® II only. NOTE: Hand tighten valve, do not overtighten.

APFA-NZL – Sold Individually



ACE® POWER FLUSH® KIT (APFK)*

Complete and easy-to-use Power Flush® Kit includes the ACE® Flush Injection Tank, 16 oz. Power Flush® and Hose / Injection assembly. The unique injection gun system saves time when flushing and eliminates manifold gauges and the use of separate access valves. One time purchase flush tank simply refills with Power Flush® cans above. Uses dry nitrogen propellant – not included. Ideal for flushing sets after conversion to 410A Refrigerant. Fits lines up to 1 1/2" diameter.

APFK – Sold individually REFILL AVAILABLE: Order APF16 for refills



POWER FLUSH® INJECTION GUN

Simple to use injection gun for use with both Power $\mathsf{Flush}^{\circledast}$ systems. Fits lines up to 1 1/2" diameter.

APF-GUN - Sold Individually

*Cone tip may be purchased seperately.



POWER FLUSH® II KIT (APFA1K)*

Complete kit combining ready-to-use, prepressurized can containing non-flammable, ozone friendly, non-toxic flushing compound and injection valve; injection gun and hose. ACE® Power Flush® II Kit is designed to flush HVAC/R systems after compressor burn-outs and during retrofits/oil changes. Ideal for "saving" linesets for 410A conversions. Non-residual solvent safe for use with all oils and refrigerants.

APFA1K – Sold Individually

Refill Available: Order APFA1 for refills

*Made with Dupont[™] Vertrel® XF Specialty Fluid Cleaner. Vertrel® is a registered trademark of Dupont[™]



POWER FLUSH® HOSE

Durable, flexible 24" charging hose with screw on connections for use with both Power Flush® systems.

APF-HOSE – Sold Individually



6

COIL CLEANERS

ALKALINE (NON-ACID) FOAMING



ACE® FOAM N' CLEAN® (FNC)

Super high foaming, deodorized, biodegradable, alkaline coil cleaner recommended for cleaning and brightening aluminum finned cooling and heating coils. The strong foaming action penetrates beneath contamination and pushes dirt and grease from the coil to the outer surface. USDA authorized for use in federally inspected plants. Dilution rate of 1 part product to 4 parts water. For Professional/Industrial Use Only.

FNC1	-	1 gallon - 4/cs
FNC2.5	-	2.5 gallon - 2/cs
FNC5	-	5 gallon
FNC55	-	55 gallon
FNC-PP	-	32 oz - 12/cs (Concentrate)



ACE® MASTERCLEAN COIL CLEANER (MCC)

A high performance, controlled foaming cleaner formulated with additional surfactants/penetrants to ensure maximum cleaning/brightening of heavily soiled aluminum finned cooling/heating coils, condensers and evaporators. Contains a deodorant for enhanced use on residential evaporators. USDA authorized for use in federally inspected plants. Dilution rate of 1 part product to 4 parts water.

MCC1	-	1 gallon - 4/cs
MCC5	-	5 gallon
MCC55	-	55 gallon



ACE® ALKALINE COIL CLEANER (ACC)

Economy grade foaming non-acid product recommended for cleaning aluminum finned cooling and heating coils. Strong foaming action penetrates contamination and pushes dirt and grease from the coil to the outer surface. Dilution rate 1 part product to 4 parts water.

ACC1	_	1 gallon - 4/cs
ACC5	-	5 gallon
ACC55	-	55 gallon



For best results when treating indoor coils to solve IAQ problems, ACE® recommends a THREE-STEP PROGRAM.

- 1. CLEAN the coil with an approved coil cleaner such as ACE[®] Super D[™] (ASD) no-rinse coil cleaner.
- 2. DISINFECT the coils and drain pans with ACE® EVAP-GARD (AEG) to eliminate and control the growth of mold, mildew and bacteria. etc.
- 3. PROTECT the drain pan (after cleaning the pan) with ACE® Pan Protectors (TR) for long lasting protection.

ALKALINE (NON-ACID) FOAMING



ACE® SUPER D™ (ASD)

High performance triple action cleaner for both evaporator and condenser coils. Cleans, degreases and deodorizes. Contains inhibitor to prevent attack on aluminum. Low foam action. "No-Rinse" at 1 part product to 10 parts water ratio. Use at a 1 to 6 dilution rate for condensers and other applications.





ACEBRITE® (ABP)

A premium, ultra high foaming, biodegradable, alkaline coil cleaner recommended for cleaning and brightening exterior condenser coils. Newly developed surfactant package creates superior foam designed to push grease, grime and dirt to coil surfaces. Dilution rate of 1 part product to 4 parts water.

ABP1 – 1 gallon – 4/cs ABP2.5 - 2.5 gallon - 2/cs ABP5 - 5 gallon ABP55 - 55 gallon

DETERGENT BASED



ACE® EVAP-KLEAN NON-RINSE **EVAPORATOR COIL CLEANER (CCL)**

Our original non-acid formulation for cleaning multi-row evaporator coils in heating and air conditioning units. Also suitable for cleaning electronic air filters and permanent air filters. USDA authorized for use in federally inspected plants. Dilution rate 1 part product to 4 parts water or 1:7 ratio when allowing condensate to rinse off.

CCL1 - 1 gallon - 4/cs CCL5 - 5 gallon CCL55 - 55 gallon

CCL-PP - 32 oz - 12/cs (Concentrate)



ACE® KLEAN HD (HDC)

Formulated especially for cleaning heavy concentrations of grease and dirt from fans, evaporators, condensers, permanent-type air filters and electronic air filters. Dilution rate of 1 part product to 4 parts water.

HDC1 - 1 gallon - 4/cs HDC5 - 5 gallon HDC55 - 55 gallon

For further product use instructions/information, refer to the Product Data Sheets or SDS Sheets at www.acechempro.com, or call 1-800-929-2436.



7

Denotes DOT hazardous product subject to UPS/FedEx shipping surcharges.

COIL CLEANERS

ACID (FOAMING)



ACE[®] CLEAN N' BRITE COIL CLEANER (CNB)



User-friendly non-foaming safe acid coil cleaner for cleaning and brightening of evaporator coils, air-cooled condenser coil, and other cooling and heating coils. The proven blend utilizes acid replacement technology and surfactants is suitable for use in both indoor and outdoor applications. Excellent scale remover. Safe Alternative to Supreme Coil Cleaner

CNB1 – 1 gallon - 4/cs CNB2.5 – 2.5 gallons - 2/cs CNB55 – 55 gallons

ECO-FRIENDLY (GREEN) COIL CLEANERS



ACE® ECO-POWER (EKP)

Concentrated, non-foaming, heavy-duty condenser coil cleaner and degreaser recognized for "SAFER CHEMISTRY" under the EPA's Safer Choice Program. Manufactured from eco-friendly Solvents & Surfactants and formulated to clean remove dirt, grime and grease from aluminum coils. Can also be safely used on evaporator coils. Excellent for use on microchannel coils.



OEM Approved...deemed safe and approved for use to clean round tube aluminum coils.



MINI-SPLIT COIL CLEANER



ACE® MINI-SPLIT C&D (MSCD)


A ready-to-use, foaming, non-rinse, mini-split coil cleaner formulated with a unique blend of neutral pH biodegradable surfactants and solvents formulated to clean and remove grease, grime, oil and other contaminants from the external surfaces of mechanical parts such as evaporators, heat pump units and permanent air filters. ACE® MINI-SPLIT C&D is manufactured from the same ingredients that have been OEM tested to be safe on aluminum evaporator coils.

MSCD - 32 oz. - 12/cs



ACE® EVAP-KLEAN PLUS (FEK)


A ready-to-use, foaming, non-rinse, coil cleaner formulated with a unique blend of biodegradable surfactants and solvents specifically formulated to clean and degrease evaporators, heat pump units and permanent air filters. Excellent for use on microchannel coils. ACE[®] EVAP-KLEAN PLUS recognized for "SAFER CHEMISTRY" under the EPA's Safer Choice Program.



OEM Approved...deemed safe and approved for use to clean round tube aluminum coils.

OEM tested for compatibility with Duro-Last roof membranes. Follow membrane manufacturer's rinse instructions





Safer Choice is EPA's label for safer chemical-based products. Every chemical, regardless of percentage, in a Safer Choice-labeled product is evaluated through EPA's rigorous scientific process and only the safest ingredients are allowed. For over 15 years, the program has labeled products that are safer for families, pets, workplaces, neighborhoods, and the environment. The label represents leadership in safer product formulation.

Ace.

AFER

CHOICE

nov/saferchoice



For further product use instructions/information, refer to the Product Data Sheets or SDS Sheets at www.acechempro.com, or call 1-800-929-2436. Denotes DOT hazardous product subject to UPS/FedEx shipping surcharges.



LEAK DETECTION



ACE® FAST FIND LEAK DETECTOR (FFD)

Polymer-based formulation, supplied in a spray bottle for ease of use. Locates even microscopic air/gas leaks.

FFD32 - 32 oz. - 12/cs FFD1 - 1 gallon - 4/cs





ACE® GAS LEAK DETECTOR (LD) Bubble forming liquid with an iridescent hue for improved visibility. This high viscosity formulation provides positive leak detection for refrigeration, air and gas lines.



LD8 - 8 oz. - 12/cs



ACE® FAST FIND LT LEAK DETECTOR (FLT)

Low temperature, polymer-based leak detector formulation suitable for use in temperatures down to -5°F.

FLT32 - 32 oz. - 12/cs



ACE® SMOKE BOMBS (ASB)

Non-explosive smoke bombs for testing heat exchangers and ductwork airflow. Part# ASB30 yields 30 seconds / 4000 cubic feet of smoke; Part# ASB60 yields 60 seconds / 8000 cubic feet. Smoke is white/gray in color.

ASB30 - 30 second - 12/box ASB60 - 60 second - 12/box







ACE® ORANGE MONSTER

Newly developed, ultra-high foaming, biodegradable, alkaline coil cleaner which cleans and brightens aluminum finned cooling and heating coils. Formulated to quickly and easily foam out dirt, oil and grease etc from deep within the coil to the coil surface where contamination can be quickly flushed from the coil surface with a clean water rinse. For Professional/Industrial Use Only.

SD1 – 1 gallon – 4/cs SD2.5 – 2.5 gallon – 2/cs SD5 – 5 gallon

SD55 – 55 gallon (Concentrate)

ACE[®] ORANGE MONSTER AEROSOL

OM-AE- 19 oz. net – 6/cs OEM Approved...deemed safe and approved for use to clean round tube aluminum coils.



ACE® MICRO MONSTER AEROSOL

MM - 19oz. net - 6/cs

0 Ace

For further product use instructions/information, refer to the Product Data Sheets or SDS Sheets at www.acechempro.com, or call 1-800-929-2436. Denotes DOT hazardous product subject to UPS/FedEx shipping surcharges.



ACE® ORANGE MONSTER WATERLESS WIPE CLEANERS

Waterless wipe cleaners is formulated to cut through grease, tar, ink, oils and adhesives. Ideal for cleaning tools, hands or machinery etc. The wipes provide industrial strength cleaning power ... but are fortified with emollient and are gentle on skin and won't crack or dry hands. The textured side of the wipe is ideal for scrubbing tough soils, while the smooth side wipes surfaces clean leaving a pleasant citrus fragrance and no residue on the surface.

MONSTER 95020 - ORANGE - 70 wipes per container - 6/cs



ACE[®] MONSTER TOWEL SO TUFF WIPING CLOTH

High performance wipe made from patented Dupont Sontara™ technology. This standard 12"x16.5" reusable, solvent resistant, high performing, super tough wipe is bigger, more durable and less expensive to use per task than paper.

ACE95030 - 75 wipes per box





ACE® MONSTER SEAL RAPID RESPONSE

Denotes DOT hazardous product subject to UPS/FedEx shipping surcharges.

Rapid Response Leak Sealant was developed to seal leaks in units which were losing gas so quickly that a faster response was required. Rapid Response is capable of sealing leaks in systems losing up to 100% of the charge within 72 hours. Current products on the market typically seal leaks losing up to 15% of the charge within 7 days. The product is formulated to work on the molecular level to create a bond to the metal surface within the unit where the leak occurs. This reaction creates a stronger, faster seal in these low- and high-pressure systems than ever before attainable. Compatible with all refrigerants ... do not use in ammonia or CO2 systems.

MNSTRSEAL (2-10 tons) - 6/cs MNSTRSEALUV (2-10 tons) - 6/cs



MATCH THE RIGHT CLEA





	· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·			
			APPLICA	TION				
Condenser Coils	Y	Y	Y	Y	Y	Y		
Evaporator coils				Y	Y			Y
Permanent Air Filters				Y	Y			Y
Electronic Air Filters					Y			
Small Condensers	Y	Y	Y	Y	Y	Y	Y	Y
Small Evaporators								
Fan Blades, Motors								Y
Rubber rooftop Units (see below)					Y			Y
			CONTAMI	NANTS		-1		
Grease Dirt & Oil	Y	Y	YY					
Cooking Grease/Oil	YY	YY	YY					
Dirt and Grime	Y	Y	Y					
Tobacco Tars					YY			
Lint/Dust	Y	Y	Y	Y	Y	Y	Y	Y
Oxide Deposits	Y	Y	Y	Y		Y	Y	
Cottonwood	Y	Y	Y	Y	Y	Y	Y	Y
Dead Bugs	Y	Y	Y	Y	Y	Y	Y	Y
Dirty Sox Odors								
Mold & Mildew								
			PROPER	TIES				
Foaming	YYY	YYY	YY	Y		Y	YYY	
Brightening	YYY	YYY	YYY	Y		YY	YYYY	
Degreasing	YY	YY	YYY	YYY	Y	Y	YYY	YYY
Non-Rinsing (Evaporators)								Y
Coil Protection				Y				
Biodegradable	Y	Y	Y	Y	Y	Y	Y	Y
USDA Authorized	Y		Y		Y	Y		
EPA/NSF Registered								
** Rubber Roofe - extreme caution must be	o upod whon oloon	ng olo unito on ruhk	or roofo Any ooil ol	onor or wooh off w	ator coming in conto		and much he works	1

** Rubber Roofs - extreme caution must be used when cleaning a/c units on rubber roofs. Any coil cleaner or wash off water coming in contact with rubber surfaces must be washed off immediately

	FOAM N CLEAN®	ACEBRITE [®]	MASTERCLEAN	SUPER D™	ACE-KLEAN HD
COLOR	Brown	Blue	Pale Brown	Amber	Yellow
Description	Alkaline	Alkaline	Alkaline	Alkaline	Alkaline
рН	13.00-13.50	13.25-13.60	13.25-13.6	13.25-13.70	13.25-13.50
Equipment to be Cleaned	Air Cooled Condenser Coils	Air Cooled Condenser Coils	Evaporator Coils, Air Cooled Condenser Coils	Evaporator Coils, Air Cooled Condenser Coils	Electronic Cells, Permanent Filters, Air Cooled Condenser Coils
Contaminants	Dirt/Grease	Dirt/Grease	Dirt/Heavy Grease	Dirt/Oil/Grease	Dirt/Grease/Nicotine
Dilution Rate	3 or 4-1	3 or 4-1	3 or 4 4-1	3 or 4-1; 10-1	4-1; 40-1
Contact Time	5-7 minutes	5-7 minutes	5-7 minutes	5-7 minutes	5-7 minutes
Rinse Required	Yes	YES	YES	YES No @ 7 -1	YES
Hard H20 Tolerance	Excellent	Excellent	Excellent	Excellent	Excellent
Biodegradable	Yes	Yes	Yes	Yes	Yes
Features	Cleans, brightens penetrating strong foam	Cleans, brightens penetrating high foam	Cleans, brightens controlled foam, excellent degreaser	Degreases, Deodorizes, detergent base. Inhibited action, low foam	Cleans, degreases. Excellent for tobacco tar/ocdor
	USDA Authorized		USDA Authorized	action, 100 10am	USDA Authorized

NER WITH THE CLEANING JOB

1

				enter C					
—		-		. 🔶		-	—	-	-
				APPLI	CATION				
Y	Y				Y			Y	
Y	Y	Y	Y	Y	Y		Y	Y	
Y	Y				Y		Y	Y	
Y	Y				Y	Y		Y	Y
		Y			Y		Y	Y	
Y	Y	Y	Y	Y	Y				
Y	Y								
				CONTA	MINANTS			N	
		YY			Y	Y		Y	
		YY Y			Y Y	Y Y		Y	
		Y			Y	Y		Ý	
Y	Y	Ŷ	Y	Y	Y	Y		Y	
I	I	I	I	I	I	I		I	
Y	Y	Y	Y	Y					
		•	1	•					
								Y	
							у	y	
PROPERTIES									
		YY	YYY	YYY		YYY			
			Y	Y		YYY			
YYY		YYY	YY	YY	YYY	YY			
Y		Y	Y	Y	Y			Y	
					Y				Y
Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
		Y							
Safer Choice	Safer Choice			NSF			Y	Y	
** Dirty Socks 0	dors - clean evapora	ator coil as usual, th	en flood surface® v	with Evap-Guard. Le	ave on surface® for	8-10 minutes then	flush off with water		

ALKALINE CC	SUPREME	EVAP-KLEAN	ECO-KLEEN	ECO-POWER	EVAP-GARD
Blue	Pink	Green	Green	Yellow	Clear
Alkaline	Acid	Alkaline	Neutral	Alkaline	
13.25-13.50	1.00-1.05	12.70-13.20	7.00-8.00	8.00-10.00	12.00-12.60
Evaporator Coils, Air Cooled Condenser Coils	Air Cooled Condener Coils	Evaporator Coils Air Filters, Air Cooled Condensers, Permanent Filters	Evaporator	Air Cooled Condensers Evaporators, Permanent Filters	Evaporator
Dirt/Grease	Dirt/Scale	Dirt/Dander	Oil/Grease/Soils	Dirt/Grease/Soils	Mold/Mildew/Bacteria
4-1	3-1	3-1; 7-1	3-1; 7-1	3 or 4 - 1	RTU
5-7 minutes	5-7 minutes	5-7 minutes	n/a	5-15 minutes	10 minutes for mold
YES	YES	YES No @ 7-1	YES No @ 7-1	YES	YES
Excellent	Excellent	Very Good	Excellent	Excellent	Excellent
Yes	Yes	Yes	Yes	Yes	Yes
Cleans, brightens medium foam	Cleans, brightens high foam	Contains corrosion inhibitor USDA Authorized	Safer Choice Green Cleaner Metal safe. Excellent for food grease/oils Safer Choice	Safer Choice GreenCleaner, metal safe. Safe for roofs/ plants etc Safer Choice	Biodegradable EPA

SELECTION GUIDE

-

AEROSOL PRODUCTS

COIL CLEANERS



ACE® FOAM BLAST (FBA)

Ultra-powerful "foam gun" aerosol spray with additional grease dissolving agents added for quick cleaning action. Ideal for use on A/C coils, oily machines, exhaust fans, etc. Fresh citrus aroma. "Non-rinse" formula for evaporators. Turn off power and eliminate any source of ignition prior to use. VOC % = 21 and % solid = 1.

FBA – 16 oz. net - 6/cs



ACE[®] FOAM N'CLEAN™ AEROSOL (FNA)

High foaming, non-acid coil cleaner removes grease, oil, dirt, etc., from aluminum-finned cooling and heating coils. Strong directional spray forces cleaner deep into multi-row coils. High foaming action flushes contamination to coil surface for easy water flush removal. Must be rinsed.

FNA - 20 oz. net - 6/cs

COIL CLEANERS





NSF registered, fragrance-free, expanding foam spray which penetrates deeply into

multi-row coils to quickly breakdown grease, grime and oil contamination ... thereby ensuring easy removal. The waterbased foam creates no harsh vapors or odors and is suitable for use in restaurants, kitchens and other occupied commercial/residential buildings. Formula OEM approved for use on microchannel coils as well as copper tube and aluminum coils. Use to clean metal surfaces such as grills, exhaust hoods and washable filters.

	APC –	19	oz.	net	-	6/cs
--	-------	----	-----	-----	---	------



SPECIALIZED COATINGS



ACE® FOAMING COIL CLEANER (FCA)

Non-acid, thick foaming, non-flammable aerosol suitable for use in hard access areas and small jobs. Ideal for condenser and evaporator coils, walk-in coolers, ventilators, refrigerators, etc. "Non-rinse" formula for evaporators.

FCA - 19 oz. net - 6/cs

OEM Approved...deemed safe and approved for use to clean round tube aluminum coils.



ACE® CONDENSERKOTE (CKA)

High-quality polyelastomer coating protects A/C aluminum finned tube coils, A/C cabinets, compressors and all nonelectric components in the A/C system from corrosion, salt air spray, acid rain, etc., with a tough, durable film that will not crack or peel. Affect on heat transfer is less than 0.1%. Coverage rate for Blue is 24 sq. ft. Coverage rate for Clear is 19 sq. ft.

CKA – Blue - 14.5 oz. net - 6/cs CKA – Clear - 14.5 oz. net - 6/cs



ACE® POWER BLAST® (CCA)

Solvent-based aerosol removes build-up of dirt, grease, etc., from all types of extended heating or cooling fins. Solvent evaporates leaving no residue. "Non-rinse" formula for condensers and evaporators.

CCA - 18 oz. net - 6/cs

*Not For Sale in California

AEROSOL PRODUCTS

INSECTICIDE PRODUCTS



ACE® WASP AND HORNET SPRAY (WHA)

EPA registered, no CFC, aerosol spray that gives rapid knockdown and kill of hornets, wasps and yellow jackets. Reaches nest more than 20 feet above ground, can be used indoors and outdoors. Provides residual kill of insects returning to the treated nest. Dielectric Breakdown Voltage: 41.0 kV by ASTM Test Method D-877-87. **EPA# 7754-44-7909**

WHA - 14 oz. net - 6/cs

LUBRICANTS



JACK OF ALL SPRAYS (JOAS)

Highly effective 4-in-1 rustbuster, lubricant, penetrant, and protectant formulated from plant-based oil. Foam spray pattern prevents drips and run off. NSF H2 and USDA certified bio-based product. Product is odorless, biodegradable and non-toxic.

JOAS25 - 2.5 oz net - 12/cs JOAS125 - 12.5 oz. net - 6/cs

COIL CLEANER & DISINFECTANT



ACE[®] EVAP-GARD PLUS (EGP)

Disinfectant cleaner, specifically for use on Small Air Conditioner Cooling Coils & Refrigeration Equipment, Refrigerator or Freezer Evaporative Coils to control bacteria, mold and mildew on pre-cleaned, hard, non-porous surfaces, when used as directed. EPA# 1839-84-7909

EGP - 20 oz. net - 6/cs



ACE[®] ROOFSEAL (RSA)

ROOF REPAIR PRODUCTS

Seals leaks, cracks, seams, etc., around rooftop airconditioning units, vents, chimneys, skylights, etc. Can also repair cracks and holes, etc., in most roofing materials. Sprays as a liquid and dries to a thick black rubberized coating.



LUBRICANTS



ACE® MECHANIC'S CHOICE (MCA)*

Chlorinated, high performance, quick-acting, high-solvency, all-purpose spray formulated to penetrate, lubricate and de-moisturize while leaving surfaces with a "never-dry" corrosion retardant.

MCA – 15 oz. net - 6/cs

*Not For Sale in CA, UT, OTC or LARDO States - CA Alternative Available

AEROSOL PRODUCTS

SPRAY ADHESIVES



ACE® HEAVY DUTY SPRAY ADHESIVE (SPA)*

Heavy-duty spray adhesive with wide web spray pattern to provide a temporary or permanent bond of materials such as duct liner, fiberglass insulation, cardboard, most plastics, polyethylene, etc. Maximum operating temperature is 110°F.

SPA - 12 oz. net - 6/cs

*Calfornia Compliant

CONTACT CLEANERS



ACE® ENERGIZED ELECTRICAL CLEANER (EEC)

A fast drying, non-residual, non-flammable, non-conductive (28kv) formulation that cleans oil, flux and other contaminants from contacts, circuit boards, switches, electric motors and electronic precision instruments. Suitable for use on energized equipment. Complies with CARB Regulations.

EEC - 10 oz. net - 6/s

CONDENSATE PAN REPAIR



ACE® PAN PATCH WHITE (PPW). BLACK (PPA). AND CLEAR (PPC)

Flexible, non-chlorinated, non-asphalt spray coating for sealing out rust, corrosion and repairing leaks in metal or plastic condensate drain pans. Can be used for repairing swamp coolers and cooling towers. Dries in 2 to 4 hours depending on heat and humidity. Coverage rate 12 to 20 square feet per can depending on thickness. Temperatures of product covered areas can reach up to 210°F before any deterioration of product occurs.

PPW - 14 oz. net - 6/cs PPA - 14 oz. net - 6/cs PPC - 14 oz. net - 6/cs

ICE MACHINE PRODUCTS

CLEANERS



ACE® NICKEL-SAFE ICE MACHINE CLEANER (NSC) Removes scale in ice machines with nickel-plated evaporators.

One 16 oz. bottle will clean a system with up to 3 gallons of sump water. NSF Registered.

NSC16 - 16 oz. - 12/cs NSC1 - 1 gallon - 4/cs





ACE® LIQUID ICE MACHINE CLEANER (LIM) Food grade acids used for all-purpose scale dissolver for fast removal of lime and scale deposits in ice machines, coffee urns,

stainless steel, etc. One 16 ounce bottle will clean a system with up to 3 gallons of sump water.

LIM16 - 16 oz. - 12/cs LIM1 - 1 gallon - 4/cs



ACE® ICE-GARD ICE MACHINE SANITIZER (AIG)

A concentrated disinfectant/virucide/sanitizer for use on ice machines. Effectively eliminates offensive odors caused by mold and mildew, while sanitizing the interior hard non-porous surfaces of ice machines. Dilute at rate of 2oz of AIG per 8 gallons of water for 200ppm sanitizing solution.

EPA# 1839-86-7909

- AIG16 16oz 12/cs AIG1 - 1 gallon - 4/cs AIG5 - 5 gallon
- AIG55 55 gallon





IAQ PRODUCTS

PREMIUM DRAIN PAN TREATMENTS



ACE® PAN-CLEAN TABS (PCT)

Forms a gel-like substance after coming into contact with condensate water that locks product in place on pan. Slowly releases cleaning agents for up to six months – thereby ensuring block and odor-free drain lines. Completely dissolves to ensure no waste disposal problems. Computer room safe.

- PCT3 treats under 3 tons 12 tabs/bottle - 12 bottles/cs
- PCT7 treats up to 7.5 tons 8 tabs/bottle - 12 bottles/cs
- PCT15 treats up to 15 tons 4 tabs/bottle - 12 bottles/cs

ACE[®] PAN PROTECTORS (TR)

EPA# 68114-1-7909

TR14 - treats 1 ton or less

TR28 – treats up to 2 tons

TR65 - treats 5 tons or less

TR150 - treats 10 tons or less

TR300 - treats up to 25 tons

TR300D - treats up to 50 tons

An EPA registered product that easily fits into most air

conditioners or refrigerator drip pans. With its controlled

release action ACE[®] pan protectors can control bacteria, mold, mildew, slime and algal growth for up to 6 months maintaining clean water and inhibiting the foul odors and blockages caused by mildew and microbial growth. Contains

odor counteractants to provide a pleasant odor as it works.

packed individually - 120/cs total

packed individually - 100/cs total

packed individually - 80/cs total

packed individually - 48/cs total

packed individually - 24/cs total

packed individually - 12/cs total

STANDARD DRAIN PAN TREATMENTS



ACE® DETERGENT TABS (DTJR)

Easy-to-use slow dissolving cleaners maintain humidifiers, condensate drains and pans in good working order while reducing odors. Formulated for use in food processing factories. Tablet size 5/8" x 1/4". Computer room safe.

DTJR - 200 tabs/bottle - 12 bottles/cs



ACE® DETERGENT TABS (DT)

Larger size drain pan tablets for commercial/industrial applications. Slow dissolving formula. Helps reduce odor and keeps pans in good working order. Tablet size 1-3/4"x1/4". Computer room safe. One tablet treats approximately 3.5 tons of system.

DT2 – 15 tabs/bottle - 12 bottles/cs DT10 – 75 tabs/bucket - 4 buckets/cs

SANITIZERS & DISINFECTANTS



ACE® EVAP-GARD (AEG)

Disinfectant spray cleans, disinfects and deodorizes in One Easy Step. This product is a non-abrasive one-step disinfectant cleaner for small air conditioner, commercial air handling unit, HVAC cooling coils and refrigeration equipment evaporation coils. **EPA# 1839-83-7909**

AEG32 – 32 oz. - 12/cs AEG1 – 1 gallon - 4/cs AEG5 – 5 gallon AEG55 – 55 gallon





Proper air filtration and clean coils are important features of any good Indoor Air Quality program. In addition, it is important to ensure that the wet confines of the condensate drain pan are protected against microbial growth.

ACE® Pan Protectors (TR) are widely used by maintenance departments in school systems, airports, hospitals, hotel chains, etc., throughout the U.S. as part of a comprehensive Indoor Air Quality program.





CONDENSATE PAN MAINTENANCE



BLOCK BUSTER (ABB) Concentrated blend of potassium hydroxide and surfactants formulated to quickly remove grease, oils, hair and organic matter from all types of drains and drain lines. Quickly remove blockages & maintains drain lines. Ideal for use in condensate, kitchen & bathroom drain lines.

ABB32 - 32 oz - 12/cs ABB1 - 1 gallon - 4/cs ACE® Block Buster See Below



2 40.00 2000 213

100

HOSES, MANIFOLDS, GAUGES & ACCESSORIES

Hoses		Manifold & Gauges	Accessories
STANDARD	ACE-60RBY 5ft standard hose	ACE-R3M4 R22 / R404A / R410A - Manifold Only	ACE-AB45 Anti-Blow Back - 45° Adapter, 1/4" FFL x 1/4" MFL
\sim	ACE-72RBY 6ft standard hose	ACE-R3M460 R22 / R404A / R410A Manifold w / (3) 60" Hoses, Red / Blue / Yellow	ACE-51645 Standard - 45° Adapter, 5/16" FFL x 1/4" MFL
ABB (LOW LOSS)	ACE-AB60RBY 5ft ABB (Low Loss) hose	ACE-R3M2 R22 / R134A / R404A - Manifold Only	ACE-AB51645 Anti-Blow Back - 45° Adapter, 5/16" FFL x 1/4" MF
	ACE-AB72RBY 6ft ABB (Low Loss) hose	ACE-R3M260 R22 / R134A / R404A Manifold w / (3) 60" Hoses, Red / Blue / Yellow	
BALL VALVE	ACE-BV60RBY 5ft Ball Valve hose	ACE-RM8 R32 / R454B, Includes Manifold only	
100	ACE-BV72RBY 6ft Ball Valve hose		
11	ACE-6BVRBY 6" Ball Valve hose		
		40 200	400

ADDITIONAL ACCESSORIES AND GAUGES AVAILABLE UPON REQUEST

For further product use instructions/information, refer to the Product Data Sheets or SDS Sheets at www.acechempro.com, or call 1-800-929-2436.

Denotes DOT hazardous product subject to UPS/FedEx shipping surcharges.

REFRIGERANT MANIFOLD R32/454B

ce.

ODOR CONTROL/MISCELLANEOUS



ACE® FRESH-AIRE (AFA)

Fast-acting liquid containing a malodor counteractant to chemically neutralize unpleasant odors commonly associated with HVAC systems. Contains a "lavender" fragrance formulated to leave the HVAC system with a pleasant fresh scent after the cleaning procedure.

AFA32 - 32 oz. - 12/cs (Spray)



ACE® ODOR NEUTRALIZER (ON1 and ONjr)

A powerful odor absorbent which quickly neutralizes odors by an ionization process. To use, simply open can and leave in area to be treated. Smaller 1-3 ton units or small areas will use ONjr (pint size), larger units and areas use ON1 (quart size). Not an odor cover-up, but does contain a pleasant wintergreen scent. Common uses include musty/ stale air, animal odors, water/fire damage odors, smoke odors and many more. Can be inserted into HVAC air stream or used in a stand alone application. Effective up to 10 weeks.

ONjr – pint - 12/cs ON1 – quart - 12/cs



ACE® HEAT SHIELD (HSG)

Environmentally safe, biodegradable, non-toxic, noncorrosive protective barrier that retards against heat transfer through metal during soldering/welding applications. Effective up to 7500°F.

Heat Shield Spray Gel: HSG32 - 32 oz. - 12/cs

SCALE REMOVERS



ACE® SCALE REMOVER (SR)

Easy-to-use inhibited acid-based scale remover with pH color indicator. Safe for use on copper, iron, steel, brass, wood, rubber and plastic equipment in heat exchangers, cooling towers, air conditioning equipment, etc. Product will mechanically remove any sludge attached to the scale growth. Use 1 gallon to 15 gallons water for heavy scale, 1 to 20 for medium to light scale. Descaling in a typical system cleaned will take roughly 4-5 hours before draining and refilling. Comes with pH test strips packet for use when neutralizing. To inhibit future scale build-up, use ACE® NCT corrosion inhibitor.

SR1 –	1 gallon - 4/cs
SR5 –	5 gallon
SR55 –	55 gallon



20

ACE® SILICA SCALE REMOVER ADDITIVE (SSA)

For extra-hard-to-remove silica scale, add to the SR solution in the above cleaning procedure. Add 1 pound of powder to each gallon of SR required for system cleaning. If unsure of scale type, ACE® can analyze a sample of hardened scale sent to the factory. Call for details.

SSA - 10 lb pail - sold individually



SCALE REMOVERS

ACE® CONDENSER CLEANER (CC-10)

Original acid detergent powder is inhibited against chemical attack on iron, galvanizing, brass and copper, etc. Removes scale, rust and sludge. 10 lbs. of CC-10 treats 50 gallons of water.

CC10-40 - 10 lb. box - 4/cs CC10-50 - 50 lb. box CC10-100- 100 lb. box


ACE® SCALEMASTER (LSR) Organic salt-based limescale remover with newly developed Acid Replacement Technology produces a safer-than-acid, fast-acting limescale (calcium carbonate) remover. Contains an inhibitor to prevent attack on aluminum, galvanizing, copper or iron. 1 gallon treats 20 gallons of water. Ships DOT non-hazardous for ground shipments.



LSR1 - 1 gallon - 4/cs LSR5 - 5 gallon LSR55 – 55 gallon

DEGREASING SOLVENTS/OIL ABSORBENTS

DEGREASING SOLVENTS



ACE® ENVIRO-KLEAN DEGREASING SOLVENT (NCD)

Non-chlorinated degreasing solvent that is ideal to remove oil, grease, etc., from air conditioning and refrigeration parts and accessories.

NCD55 – 55 gallon

ALKALINE DEGREASER



ACE® SUPERKLEAN (SKL)*

High performance, concentrated alkaline general purpose cleaner and degreaser quickly and easily removes heavy concentrations of grease, dirt, grime, waxes etc., from appliances, grease filters, motors, engines, etc.

 SKL32
 32 oz. 12/cs

 SKL1
 1 gallon 4/cs

 SKL25
 2.5 gallon 2/cs

 SKL5
 5 gallon
 2/cs

SKL55 – 55 gallon

*Not Compliant For Sale in CA.

OEM tested for compatibility with Duro-Last roof membranes. Follow membrane manufacturer's rinse instructions



ACE[®] SUPER DEGREASER (DGA)

A heavy-duty, quick dry, non-residual, degreasing solvent that dissolves grease, grime, oil and other oilbased contaminants on mechanical parts, refrigerant systems, oil burner parts etc. Safe on most metals. While safe on most plastics ... always test in an inconspicuous area before use. Not for use on electrical equipment.

DGA - 15oz net - 6/cs

*Not For Sale in California.



COIL CLEANERS

ACE® POWER BLAST® (CCA)

Solvent-based aerosol removes build-up of dirt, grease, etc., from all types of extended heating or cooling fins. Solvent evaporates leaving no residue. "Non-rinse" formula for condensers and evaporators.

CCA - 18 oz. net - 6/cs

*Not For Sale in California

OIL ABSORBENTS



ACE[®] OIL ABSORBENT PADS (WFMF100)

Polypropylene fiber absorbent pads pick up all types of industrial oils while not absorbing water. Size 17"x19".

WFMF100 - 100/pkg



ACE® FOAM BLAST (FBA)

Ultra-powerful "foam gun" aerosol spray with additional grease dissolving agents added for quick cleaning action. Ideal for use on A/C coils, oily machines, exhaust fans, etc. Fresh citrus aroma. "Non-rinse" formula for evaporators. Turn off power and eliminate any source of ignition prior to use. VOC % = 21 and % solid = 1.

FBA - 16 oz. net - 6/cs



21

HEAT TRANSFER & ANTI-FREEZE PRODUCTS

FROSTSAFE / PIPESAFE



%

Ethylene

Glycol

Needed

16%

26%

34%

40%

45%

49%

53%

56%

60%

% PG or

PG Food

Grade

Needed

20%

29%

37%

43%

48%

52%

56%

58%

60%

Freeze

Protection

Point

+20

+10

0

-10

-20

-30

-40

-50

-60

An inhibited glycol-based anti-freeze suitable for protection of closed systems against severe weather conditions. Available in ethylene or propylene glycol. Glycol products are available with or without inhibitors subject to customer requests.



Frostsafe (Ethylene Glycol)

EG5	-	5 gallon
EG55	_	55 gallon

Pipesafe (Propylene Glycol)

PG5	-	5 gallon
PG55	-	55 gallon

Pipesafe Plus (Propylene Glycol Food Grade)

PG55FG - 55 gallon

PG Food Grade, 55 gallon only:

(Must be used in applications where product may come in contact with food.)

All ACE® glycols are 100% virgin material no recycled material is used. Only deionized water is used in MFG.



Freeze

Protection

Point

+20

+10

0

-10

-20

-30

-40

-50

-60

%

EG60

Needed

28%

43%

56%

66%

76%

83%

90%

93%

100%

%

PG60

Needed

33%

48%

60%

71%

80%

86%

88%

95%

100%

Freeze

Protection

Point

+20

+10

0

-10

-20

-30

-40

-50

-60

An inhibited 60% glycol-based antifreeze which provides burst protection to -100° Fahrenheit. Available in ethylene or propylene glycol.



Frostguard (Ethylene Glycol)

EG60-1	-	1 gallon - 4/cs
EG60-5	-	5 gallon
EG60-55	_	55 gallon

Pipeguard (Propylene Glycol)

PG60-1	-	1 gallon - 4/cs
PG60-5	-	5 gallon
PG60-55	-	55 gallon

Available in all dilution rates

GLYCOL REFERENCE GUIDE								
ACE® PRODUCT	DESCRIPTION	%	•	COMPETITION				
		*	Nucalgon	Virginia	Diversitch	Houghton	Noble	Hercules
FROSTGUARD					•	·	·	
EG40	Ethylene Glycol	40%		* * *	Pro-Tek Eg 40	•	* * *	
EG50	Ethylene Glycol	50%	•	•	Pro-Tek Eg 50	- - - -	• • •	
EG60	Ethylene Glycol	60%	•	• • •	e e e e	* * *	* • •	
FROSTSAFE			÷				·	
EG100	Ethylene Glycol	95%	Freez-Therm (96%)	•	Pro-Tek Eg		•	
PIPEGUARD				·	·		·	
PG40	Ind Grade Propylene Glycol	40%	Burst-Kontr'l (40%)	• • •	Pro-Tek 50 (35%)	• • •	• • •	
PG50	Ind Grade Propylene Glycol	50%	•	*	* * * *	- - - -	• • •	Cryo-Tek Original
PG60	Ind Grade Propylene Glycol	60%	• • •	Pipesaver	e • •	Wintrex	No Burst	
PG70	Ind Grade Propylene Glycol	70%	Freez-Kontr'l	- - - -	Pro-Tek 100 (70%)	•	*	Cryo-Tek
PIPESAFE								
PG100	Ind Grade Propylene Glycol	95%		•	Pro-Tek Plus	Safe-T-Therm	Super No Burst	Cryo-Tek Ag
PIPESAFE PLU	S*		•					
PGFG100	USP Grade Propylene Glycol	100%		•	•		•	

*Inhibitor Package Can Be Sold Separately



SHOP TOWELS & WIPES

MAINTENANCE



ACE® WHITE TERRY TOWELS (WTT)

Grade "A", standard 13"x12" extra absorbent cotton terry towels that are washable and reusable. Pre-washed for softness and absorbency.

ACE10700 – #5 Box (approx 25 towels) ACE10750 – 12 pack cellophane wrap

MAINTENANCE/SAFTEY



SO TUFF WIPING CLOTH (OTWC)

High performance wipe made from patened Dupont Sontara™ technology. This standard 12" x 16.5" reusable, solvent resistant, high performing, super tough wipe is bigger, more durable and less expensive to use per task than paper.

ACE95000 - 75 wipes per box



HUCK (SURGICAL) TOWELS

Pre-washed, lint-free 100% cotton "huck" towels. Standard 16"x24" with sewn edges for added strength and durability.

ACE21005 - #5 box (net 4lb of towels)



MIXED WHITE KNITS (MWK)

All purpose, economical white t-shirt and mixed knit rags are super absorbent and soft.

.

95010 - #5 box (net 4lb of wipes)



RED SHOP TOWELS (RST)

Pre-washed general purpose 100% cotton shop towel. Standard 14"x14" washable and reusable with sewn edges for strength and durability.

ACE32025 - 25 count poly bag





THREADED PIPE PRODUCTS



ACE® ALL-PURPOSE PIPE DOPE (APD)

Brush-in-can, yellow, non-hardening, non-toxic pipe joint compound for use on all metals, ABS, PVC, CPVC, etc. Does not contain lead or silicone.

APD8 - 8 oz. - 24/cs APD16 - 16 oz. - 12/cs



ACE[®] PIPE SEAL (TPD)

Teflon-based, brush-in-can, non-hardening, yellow pipe compound for use on metal and plastic threaded connections. Does not contain lead or silicone. VOC 356.4 g/l.

TPD8 - 8 oz. - 24/cs TPD16 - 16 oz. - 12/cs



ACE® TEFLON TAPE (ATT)

White teflon tape ensures tight fits for threaded connections.

ATT - 100 rolls/cs



ACE® WET/DRY PVC CEMENT (WPVC)

Extremely fast drying, blue, medium bodied PVC cement recommended for wet and/or quick pressurization conditions. Suitable for joining PVC pipe and fittings for all class and schedule pipe up to 6" circumference; schedule 60 up to 4". VOC \leq 510 g/l. Ideal temperature 40°-110° F.

WPVC8 - 8 oz. - 24/cs WPVC16 - 16 oz. - 12/cs

.....



ACE® PVC CEMENT (PVC)

Dauber-in-cap, regular bodied medium-to-fast setting PVC cement for PVC pipes and fittings. Suitable for use for schedule 40 and 80 pipes up to 4" in diameter. Low VOC \leq 510 g/l. Clear in color.

PVC8 - 8 oz. - 24/cs PVC16 - 16 oz. - 12/cs

.....



ACE® PVC PRIMER /CLEANER (PVCP)

Clear, dauber-in-cap formula cleans, primes and softens pipe and fittings prior to application of solvent for secure bonding of surfaces. Purple in color.

PVCP8 - 8 oz. - 24/cs PVCP16 - 16 oz. - 12/cs



ACE® INSULATION ADHESIVE (INA)

A high-strength, white-colored, contact cement suitable for use in bonding pipe insulation tubes/sheets and most other clean, dry surfaces. Dries flexibly to form a positive vapor barrier to prevent pipe sweat and heat transfer.

INA8 - 8 oz. - 24/case INA16 - 16 oz. - 12/case INA32 - 32 oz. - 12/case

24 Acce For furth

For further product use instructions/information, refer to the Product Data Sheets or SDS Sheets at www.acechempro.com, or call 1-800-929-2436. Denotes DOT hazardous product subject to UPS/FedEx shipping surcharges.

REFRIGERATION OIL PRODUCTS

MINERAL OILS

BVA REFRIGERATION OIL (NAPHTHENIC)

Manufactured and refined by the Calumet Refining Company, **BVA** refrigeration oils are OEM approved and used by major compressor manufacturers. The oils offer excellent chemical stability when in the presence of refrigerant and other compressor materials. The oils also have good thermal stability to ensure good performance at high temperatures and have good low temperature properties to prevent congealing in the evaporator. The oils are also wax-free to prevent floc problems in the evaporator and expansion valve. OEM approved.

	Quart 12/cs	Gallon 6/cs	5 Gallon	55 Gallon
BVA 3 150 SUS	BVA3 - 32	BVA3 - 1	BVA3 - 5	BVA3 - 55
BVA 4 300 SUS	BVA4 - 32	BVA4 - 1	BVA4 - 5	BVA4 - 55
BVA 5 500 SUS	BVA5 - 32	BVA5 - 1	BVA5 - 5	BVA5 - 55

OEM Compressor Approvals: Copeland, Prestcold, Dunham Bush, Tecumseh, Trane, Carlyle, Schnacke-Grasso.

ALKYL BENZENE OILS

BVA, AB OILS (BVA, AB)

A wax-free, alkylated benzene-based lubricant, that does not contain paraffin chains that cause floc properties. **BVA Alkyl Series** has excellent miscibility with R-22. The **BVA Alkyl Series** is miscible with some of the new interim refrigerants such as MP-39, MP-52, MP-66, HP-80 and HP-81. It also makes retrofitting easier and more effective. **BVA Alkyl Series** oil offers excellent thermal stability and chemical stability. Due to its compatibility with mineral oil it can be used in its place or added to mineral oil. OEM approved.

		Gallon 4/cs	5 Gallon	55 Gallon
BVA 100E	500 SUS	BVA100E - 1	BVA100E - 5	BVA100E - 55
BVA 150	150 SUS	BVA150E - 1	BVA150E - 5	BVA150E - 55
BVA 200CA	200 SUS	BVA200CA - 1	BVA200CA - 5	BVA200CA - 55
BVA 300	300 SUS	BVA300 - 1	BVA300 - 5	BVA300 - 55

OEM Compressor Approvals: Copeland (200 ca), Danfoss, Tecumseh, Carrier / Carlyle, Bristol. and others.



POLY VINYL ETHER OILS

BVA PVE OIL

A new synthetic polyvinyl ether lubricant, exhibits excellent performance characteristics in air conditioning and refrigeration applications, and is suitable for use with all HFC refrigerants including R-134a, R-404, R-407C, and R-410A.

	Quart 12/cs	Gallon 6/cs	-	-
PV32	PV32-Q	PV32-G	-	-
PV68	PV68-Q	PV68-G	-	-

POLYOL ESTER OILS

BVA RPOE Series is miscible with all HFC, HCFC, CFC and blends. The series was specifically developed for HFC refrigerants. OEM approved.

	Quart 12/cs	Gallon 4/cs	5 Gallon	55 Gallon
BVA POE22cc 115 SUS	BVA POE22 cc-32	BVA POE22 cc-1	BVA POE22 cc-5	BVA POE22 cc-55
BVA POE32 150 SUS	BVA P0E32-32	BVA POE32-1	BVA POE32-5	BVA P0E32-55
BVA POELT32 150 SUS	BVA POELT32 -32	BVA POELT32 -1	BVA POELT32 -5	BVA POELT32 -55
BVA POE46 200 SUS	_	BVA POE46-1	BVA POE46-5	BVA POE46-55
BVA POE68 300 SUS	BVA P0E68-32	BVA P0E68-1	BVA POE68-5	BVA POE68-55
BVA POE100 500 SUS	-	-	BVA POE100-5	BVA POE100-55
BVA POE120 600 SUS	BVA POE120-32	BVA POE120-1	BVA POE120-5	BVA POE120-55
BVA POE170 800 SUS	_	BVA POE170-1	BVA POE170-5	BVA POE170-55
BVA POE220 1000 SUS	-	BVA P0E220-1	BVA POE220-5	BVA P0E220-55

ADDITIONAL OIL PRODUCTS




BVA VACUUM PUMP OIL (VPO)

High quality multi-viscosity oil capable of performing at the deepest vacuum. Quart size bottle with easy-pour spout.

VAC235-32 – 32 oz. - 12/cs VAC235-1 – 1 gallon - 6/cs

SPRAYERS



HOSES, WATER NOZZLES

HOSES



Z-75850, Z-75875 and HW 5850

Top of the line high performance five ply construction all-weather rubber/vinyl water hoses with added durability and flexibility for extra heavy-duty use.

Z75850 – standard 5 ply - 50 foot Z75875 – standard 5 ply - 75 foot

Extra heavy-duty hot water rubber hose capable of extended hot water (200°F) use.

HW5850 - 50 foot hot water hose

WATER NOZZLES



571TFR, 573 and 474 NOZZLE

571TFR Heavy-duty hose nozzle, suitable for hot water use. Insulated comfort-grip rubber handle on steel and brass body with washer. 573 NOZZLE Zinc plated steel and brass construction hose nozzle with washer. 474 NOZZLE Plastic and brass leak-proof, shatter-proof, hose nozzle with washer.

571TFR – Sold individually 573 – Sold individually 474 – Sold individually

01RW HOSE WASHERS

High quality rubber hose washers. 01RW – 10 washers/pk





For further product use instructions/information, refer to the Product Data Sheets or SDS Sheets at www.acechempro.com, or call 1-800-929-2436. Denotes DOT hazardous product subject to UPS/FedEx shipping surcharges.

INSULATION PRODUCTS



ACE® CHIP BRUSH (ADB)

Economical 2 1/2" brush for use with ACESEAL MASTIC.

ADB - 12/cs



ACE® FOAM INSULATION TAPE (AIF)

Prevents condensation on cold pipes and can be used to minimize heat loss on hot pipes. Tape will not dry out or crack.

AIF2 - 30' x 2" x 1/8" roll - 12/cs



ACE® FIRE SEAL 136 (FSL)

Single component non-combustible material for use in single-family residential homes. Meets ASTM-E136 and ASTM-E814 standards for residential structures. Resumes fireblock rating. Red in color.

Residential Grade

FSL136 - 10.3 oz Tube - 12/cs



ACE® CORK TAPE (ACT)

Non-hardening, non-skinning rubberized cork tape designed to bond easily to piping without any additional adhesives. Manufactured for the air conditioning industry as an insulating material for hot/cold pipes and also to prevent pipe condensation.

ACT2 - 30' x 2" x 1/8" roll - 12/cs



ACE[®] FIRESTOP 814 (FST)

One part, intumescent latex based sealant meeting ASTM-E814/UL 1479 standards for commercial firestopping applications. Resumes integrity of 1 and 2 hour rated floors and walls. Forms a tough, flexible seal. Red in color.

Commercial Grade

FST814 - 10.3 oz Tube - 12/cs



ACE[®] BEAD CORDS (AB)


Non-hardening, ready-to-use, water-resistant compound ideal for sealing all joints, seams and openings. Product maintains shape and properties under a wide range of temperatures and conditions. Excellent for heated and cooled boxes.

AB - 3/8" x 25 bead cords - 12/cs



ACE® INSULATION SLUGS (ATG)

Non-hardening, ready-to-use, water-resistant compound ideal for sealing all joints, seams and openings. Product maintains shape and properties under a wide range of temperatures and conditions. Excellent for heated and cooled boxes.





HANDI FOAM (FMA JR.)

Triple expanding polyurethane foam designed to fill holes, gaps, etc., in air conditioning and refrigeration applications. Does not contain CFC's.

FMAjr - 12 oz net - 12/cs





WATER FILTRATION PRODUCTS



EVERPURE REPLACEMENT CARTRIDGES



I-2000 / I-4000

Reduce water-related ice machine problems caused by dirt. objectionable tastes and odor and by scale build-up. Precoat submicron filtration removes particles as small as 1/2 micron along with chlorine and other offensive contaminants, and the feed of 6R Micromet inhibits scale build-up caused by dissolved minerals. NSF Certified under NSF/ANSI Standards 42 and 53.

I-2000 - 9,000 gallons capacity

I-4000 - 12,000 gallons capacity



4CB5S / 7CB5S

NSF

EVERPURE REPLACEMENT CARTRIDGES

Genuine Everpure 5 Micron replacement cartridge for Standard Everpure heads. Controls scale as well as chlorine taste and odor. Maintains important NSF Class 1 Certification for Performance and Safety standards. Use for ice machine and steamer applications. Flow rate 1.67 gallons per minute.



4CB5S - 6,000 gallon capacity 14 in. long - 6/cs 7CB5S - 10,000 gallon capacity 20 in. long - 6/cs

Can replace the following Everpure cartridges: I-2000, I-4000, MH



MC2 / XC2

NSE

4CB5 / 7CB5

gallons per minute.

NSF

NSE

Reduces chlorine taste/odor and other offensive contaminants that adversely affect the taste of fountain beverages. Precoat submicron filtration removes particles as small as 1/2 micron, and help retain carbonation in drinks. NSF Certified under NSF/ ANSI Standards 42 and 53.

Genuine Everpure 5 Micron replacement cartridge for Standard Everpure heads. Controls chlorine taste and odor. Maintains

important NSF Class 1 Certification for Performance and Safety

standards. Use for drinking water applications. Flow rate 1.67

4CB5 - 6,000 gallon capacity 14 in. long - 6/cs

7CB5 - 10,000 gallon capacity 20 in. long - 6/cs

Can replace the following Everpure cartridges:

MC, QC71, XC, CV, XCV, T0 and 7DBG.

MC2 – 9.000 gallons capacity

XC2 - 12,000 gallons capacity



CUNO[®] REPLACEMENT CARTRIDGES

REPLACEMENT FOR CUNO® SERIES 8000 FILTER CARTRIDGES

E Series CU-S and CU cartridges are replacements for the CUNO Series 8000 filter cartridges in food service, vending machine and OCS applications. Both incorporate carbon block filters that polish water for high quality beverage and ice, reducing chlorine taste and other offensive contaminants.

10,000 gallon capacity Flow: 1.5 gpm

CU-S: EV9781-12 - Replaces CFS-8112S, CFS-8720S & CFS-8812S CU: EV9781-10 - Replaces CFS-8112, CFS-8720 & CFS-8812

INLINE FILTERS



INLINE FILTER FOR CHLORINE TASTE/ODOR REMOVAL

10 inch and 12 inch in-line filters with NSF Class 1 Taste and Odor reduction rating. Also reduces Limescale, Capacity of .75 GPM. Ideal for small icemakers (up to 250 lbs. capacity), coffee makers, or drinking fountains. 1/4" NPT openings. Fittings not included.

10" - IN10 - 2400 gallon capacity 10 in. long - 6/cs 12" - IN12 - 4800 gallon capacity 12 in. long - 6/cs



28

For further product use instructions/information, refer to the Product Data Sheets or SDS Sheets at www.acechempro.com, or call 1-800-929-2436. Denotes DOT hazardous product subject to UPS/FedEx shipping surcharges.

WATER FILTRATION PRODUCTS



REPLACEABLE CARTRIDGES FOR FILTER HOUSINGS



SEDIMENT CARTRIDGES (PRE-FILTER) FOR PARTICLE REDUCTION ONLY

Coarse pre-filter cartridges for bowl type systems. Reduces dirt, rust and sediment in high volume applications. Ten micron rating. Two inch diameter. Fits all standard size 5/10/20 inch bowls.

CARBON CARTRIDGES FOR CHLORINE TASTE/

Reduces chlorine taste and odors. Recommended for foodservice/ drinking water applications. NSF Class 1 Rating. Two inch diameter. Fits all standard size 5/10/20 inch bowls.

5"	-	P5-478	-	12/cs
10"	-	EC-110	-	12/cs
20"	_	EC_210	_	6/00

)" – EC-210 – 6/

ODOR REMOVAL

5" – GAC-5

NSF

10" - CGT-10 - 12/cs

20" - CGT-20 - 12/cs

.....

– 24/cs

FILTER HOUSING

COMPLETE FILTER SYSTEMS AVAILABLE IN MANY CONFIGURATIONS

Complete filter systems include single, double, or triple bowl systems complete with bowls, mounting brackets, pressure gauge and shut-off valves. Accepts any 10/20 inch long, 2 inch diameter filter cartridge.

- CGS-10 single 10" bowl system
- CGS-12 double 10" bowl system
- CGS-20 single 20" bowl system
- CGS-22 double 20" bowl system
- CGS-23 double 20" bowl system (parallel piping)
- CGS-55 triple 20" bowl housing

Cartridges sold separately





10" & 20" COARSE PREFILTERS WITH HOUSING

10" and 20" clear housings, each including a 10" and 20" replaceable prefilter cartridge. Filters out larger dirt and rust particles thereby extending the life of submicron carbon filters.

10" – EV9795-80 20" – EV9795-90

Optional: Wing Bracket for all multiple filter head systems manufactured after 2003: EV3114-34

COMPLETE FEEDER SYSTEM



SCALE CONTROL IN ICE/COFFEE APPLICATIONS

A complete system for the control of scale in ice, coffee and combination applications. It dispenses a controlled amount of HydroBlendTM compound which provides for a more consistent feed and longer life. The system includes a clear housing and one cartridge and spacer.

Part Number: EV9798-45

Optional: Wing Bracket for all multiple filter head systems manufactured after 2003: EV3114-35

EVERPURE FILTER HEADS



QC71 HEADS

Designed for all Nu-Plus Series E filters. All sizes come with a built-in shut off, flushing valve and an outlet pressure gauge which is included on the mounting bracket. (3/8 NPT)

Single:	EV9272-41
Twin Parallel:	EV9272-22
Triple Parallel:	EV9272-23
Quad Parallel:	EV9336-11



SCALE AND CARBON CARTRIDGES SCALE/ TASTE/ODOR/CHLORINE REMOVAL (ICE MACHINE)

Combination cartridges perform the job of scale removal, as well as taste and odor reduction, making them ideal for ice machine filtration. 10/20 inch long cartridges fit all brands of 2 inch diameter, 10/20 inch long housings.





TRANSLUCENT SCALE INHIBITION CARTRIDGE

The translucent cartridge allows for easy visual monitoring of the product's usage. (The IMF-10 is a longer life scale inhibition cartridge.)

IMF-7 - EV9799-32 IMF-10 - EV9799-02

For further product use instructions/information, refer to the Product Data Sheets or SDS Sheets at www.acechempro.com, or call 1-800-929-2436.



f 🖸 in 🕩

Follow us on social media

Stay in the loop with ACE on social media! Get exclusive access to step-by-step video tutorials, sneak peeks of our newest products, and unbeatable deals you won't want to miss. Follow us now and level up your style, skills, and savings—because with ACE, you're always ahead of the curve.



ACE is on YouTube

Learn how to use our products. Make sure to share as we kick off the season!



Informative

Technical

Better Result





3741 ATLANTA INDUSTRIAL PKW ATLANTA, GA 30331 800-929-2436 404-505-6626 (FAX) 404-505-9607 WWW.ACECHEMPRO.COM